

TECHNICAL CHARACTERISTICS

SELENIA WR 5W-40

PRODUCT CODE: 1092

APPLICATION

All-weather multiviscosity grade lubricant for latest generation Diesel engines. Guarantees excellent cold starting, lower consumption and maximum protection, even at low service temperatures.

SPECIFICATIONS

SAE 5W-40, API CF, ACEA B3/B4,
FIAT 9.55535-N2 CONTRACTUAL TECHNICAL REFERENCE N°F515.D06, GM-LL-B-025, VW 502.00,
VW 505.00, MB 229.3 Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,856
VISCOSITY AT 100°C	ASTM D445	cSt	15,0
VISCOSITY INDEX	ASTM D2270	--	175
FLASH POINT Cl. O. C.	ASTM D92	°C	>200
T.B.N.	ASTM D2896	mg KOH/g	10,2
POUR POINT	ASTM D97	°C	<-36
FOAM AT 24°C	ASTM D892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

05/2015